

Description

FORCE SYNTHETIC ATF is a high quality multifunction automatic transmission oil formulated from synthetic base oil and selective additives. This oil is highly recommended for automatic transmission for all kinds of vehicles, hydraulic systems and industrial engines.

Typical Result

Characteristics	Test Method	Synthetic ATF
Density at 15 °C, kg/l	ASTM D - 4052	0.8379
Kinematic Viscosity, at 40°C, cSt	ASTM D - 445	35.04
at 100 °C, cSt.	ASTM D - 445	7.425
Viscosity Index	ASTM D - 2270	186
Colour	Visual	Red
Flash Point (°C)	ASTM D - 92	240
Pour Point (°C)	ASTM D - 5950	-51

Performance Levels Force Synthetic ATF

Meets the performance level :

- General Motor Dexron®- III H (Revision)
- Ford Mercon®
- Allison C4

Superiorities

This oil provides very optimum protection against wear, corrosion, deposit control at automatic gearbox, shift gear transmission without shock, more stable friction and long life use, and prevents the varnish and sludge formation.

Applications

This Oil is most applicable for various automatic transmission for vehicles from General Motor, Ford, Detroit Diesel and Vehicles made in Japan, Korea and other countries. This oil is also applicable for power steering, automotive hydraulic system, construction and farming equipments.